



BUGATTI

VALVOSANITARIA SPA



03000337-342
 Forged brass ball valve, full port, F-F, with
 aluminium handle. Size: from 1/2" to 2"

SPECIFICATION
 PRO 03000337-342
 ISO 228/1

Assembly in rigid pipe
 Nominal pressure (PN) in bar 25-64
 KV: flowrate coefficient m³/h
 Direction of flow as desired
 Temperature range: -20 °C / +185 °C

BUGATTI PRO
 MADE IN ITALY
 ON OFF

N°	Description	Material	Treatment	Q.ty
1	Body	Brass CW617N	Nichel-plated	1
2	End connection	Brass CW617N	Nichel-plated	1
3	Handle	Aluminium GDALSI 12Cu		1
4	Upper Seal	PTFE G400		2
5	Nut	Stainless-steel AISI 304		1
6	Ball Seal	PTFE G400		1
7	Brass Ring	Brass CW614N	Crome-plated	1
8	Ball	Brass CW614N		1
9	Stem	Brass CW614N		1
10	O-Ring	Viton 01/B70FKM		1
11	Lower seal	PTFE G400		1

Designazione particolare / Name
 Valvola a sfera passaggio totale, F-F, con leva in alluminio timbrata
 BUGATTI PRO

Disegnato / Designed by
 Matteo Tavella
 Approvato / Approved by
 Renato Borghetti
 Data / Date
 23/09/2013
 Serie / Project N°
 BUGATTI PRO

Forma / Form
 A3
 Scala / Scale
 1:1
 Foglio / Tab.
 1/1
 Qualità secondo indicazioni di tolleranza
 MEDIA UNI-ISO 2768/1
 Rugosità Generale
 General Roughness
 Valuto per / Available for
 Consultazione

BUGATTI
 VALVOSANITARIA
 UFFICIO
 TECNICO

N° Disegno / Drawing No.
 03000337-342
 Revisione / Revision
 -
 Peso / Weight
 -
 Misure / Size
 g 1/2"-2"

DN	G	A	B	C	D	Ch	KV	PN
15	1/2"	50	48	87.5	10	25	16.3	64
20	3/4"	58	52	87.5	12	31	29.5	40
25	1"	69	63	131.5	14	38	43	40
32	1 1/4"	81	69	131.5	16	48	89	25
40	1 1/2"	94	86	154	17	54	230	25
50	2"	108	93	154	19	67	265	25